




www.jiademachine.com

Capsule/Tablet Blister Cartoning Line



CATALOGUE

Capsule/Tablet Blister Cartoning Line

DPP-260 is specially designed for medium size productions that require a high flexibility.

Flat platen type forming and sealing, constant sealing pressure and temperature ensure a perfect blister.

Heat forming and cold forming:

PVC, PVC+PVDC, PVC/aclar, PP, ALU-ALU.etc.

Easy changeover without tools

Up to 200 blisters/min(58×80mm)

The **JDZ-120III** cartoning machine is suitable for blister package product, adjust automatic feeding structure conveniently, setup quantity of blisters on touch screen randomly. On line product feeding and detecting, leaflet fold (1-4folds) and feeding, leaflet detecting, carton opening and forming, products and leaflet pushing into carton, printing batch number, sealing carton with tuck-in or hot melt glue device. Automatically reject lacking of leaflet or product and finished product out.



Features:


- Up to 120 cartons/min.
- Machine with GMP and cGMP standard, adopts PLC control system, servo motor drive control.
- Equipped camera detection, lack of material testing, to ensure the passing rate of finished products.
- Uses the safety cover protection devices to ensure operator safety.
- Machine can be separated to some parts, order easy move into the elevator and clean room.

leaflet folding



Tablet Feeding

Aluminum foil heat seal part



The **JDZ-120III** Capsule/Tablet Blister Cartoning Line is included **DPP-260** blister packing machine and **JDZ-120III** cartoning machine.



Technical Data	DPP-260
Output	Max.200 blisters/min
Speed	Alu/PVC, 20-50 cycles/min Alu/Alu,15-30cycles/min
Die-cutting range max.	250x120mm
Forming depth max.	15mm(or 23mm upon request)
Indexing max.	130mm
Forming foil	PVC, PVC+PVDC, PVC/aclar, ALU-ALU.etc.
Max.wide	260mm
Max.diameter	350mm
Max.thickness	300 microns
Lidding foil	Al, paper, etc.
Power supply	380V/220V 50/60Hz
Power consumption	5.7Kw
Water consumption	50 Its/hour @ 15/18℃
Air consumption	0.3m ³ /min 0.5-0.7MPa
Dimensions	L=4200mm A=650mm H=1700mm
Net weight	1500Kg

Main technical parameters		JDZ-120III
Encasing speed		120 cartons/min
Carton	Quality requirement	250-350g/m ²
	Dimension range(LxWxH)	(70-180) x(35-85) x(14-50)mm
Leaflet	Quality requirement	60-70g/ m ²
	Unfolded leaflet specification	(80-250) x(90-170)mm
	Fold range	1-4 fold
Compressed air	Working pressure	≥0.6mpa
	Air consumption	120-160L/min
Power supply		220V 50HZ
Power		0.75Kw
Machine dimension(L*W*H)		3100x1100x1550mm
Machine weight		1400kg



JIADÉ also offer:

Encapsulation Solutions

Tablet Compression Solutions

Coating Systems

Cartoning Systems

Blister Packing Solutions

